

## BT8332

### CEILING MOUNTED MENU BOARD MOUNTING SYSTEM

The BT8332 is a modular ceiling mounting system for menu board installations of any size. The BT8332 can mount screens in landscape or portrait orientations with the option for tilt adjustment up to +20° for enhanced overhead visibility, perfect for fast food restaurants. As part of the System X range, the BT8332 can be used in thousands of different configurations and must be ordered according to your requirements using B-Tech's online configuration tool (see below, right).

#### SPECIFICATIONS

Recommended screen size	<b>32" - 75"</b>
Max load	<b>50kg</b> per screen
Tilt range (tilt arms only)	<b>+20°</b>
Universal fixings	up to <b>900mm*</b>
Pole lengths	<b>0.5m</b> up to <b>3m</b> (can be cut or joined)
Colour	<b>Black</b>

#### FEATURES

- 1 Choice or fixed, tilting or pop-out interface arms to suit a range of installations
- 2 Supports landscape, portrait, and back-to-back mounting
- 3 Multiple rail lengths available (rails can also be joined to create larger installs)
- 4 Can also be mounted from the ceiling or in floor-to-ceiling configurations
- High-end aesthetic quality
- Suitable for landscape, portrait and back-to-back mounting
- Interface arms available for portrait mounting XXL screens with vertical fixings up to 800mm or 900mm
- All arms feature levelling screws to adjust the screen height
- Tilting arms offer up to +20° tilt adjustment for improved overhead visibility
- TÜV certified

### SYSTEM X



#### CREATE YOUR MOUNTING SYSTEM ONLINE

SPECIFY YOUR VIDEO WALL & MENU BOARD REQUIREMENTS  
ONLINE AND OUR SYSTEM X CONFIGURATION TOOL WILL  
CREATE A MOUNTING KIT TO SUIT YOUR NEEDS



There are thousands of System X configurations available! Visit our online configuration tool to specify setups, number of screens, number of rows and orientation.

Try now at [www.btechavmounts.com/systemx-configuration](http://www.btechavmounts.com/systemx-configuration)



RECOMMENDED MAX SCREEN	MAX LOAD	MAX VESA	MICRO ADJUSTMENT	POST INSTALL ALIGNMENT	TIPT	CONFIGURE AS REQUIRED	TÜV CERTIFIED	QR CODE
75" 190cm	50kg	900			20°		TÜV Rheinland	



\*Refers to maximum vertical fixing dimension for a typical configuration. Correctly sized interface arms and adaptors will be supplied as necessary to suit the mounting pattern you require.

